

# Foam Chambers UL LISTED

NewAge Foam Chambers are designed to introduce expanded foam directly onto the surface of a flammable or combustible liquid for fire extinguishment and /or vapour suppression. Foam Chambers with vapour seal are suitable for fixed roof tank applications. NewAge has various models of foam chambers made of carbon steel as well as stainless steel. NewAge offers complete range of UL Listed foam chambers with compatible UL listed foam deflectors. Complete range of NewAge foam chambers includes the sizes from 50, 65, 80, 100 and 150 NB with the flow discharge varying from 75-225 LPM, 225-450 LPM, 450-900 LPM, 900-1800 LPM and 1800-2700 LPM respectively. The entire range is UL LISTED.



## Specification

MODEL		FLOW CAPACITY	PRESSURE KG/CM2	UL LISTED FOAM DEFLECTOR E MODEL	
C.S	S.S			C.S	S.S
FC-50	FC-S-50	75-225 LPM	3.50	FD-80	FD-S-80
FC-65	FC-S-65	225-450 LPM	3.50	FD-100	FD-S-100
FC-80	FC-S-80	450-900 LPM	3.50	FD-150	FD-S-150
FC-100	FC-S-100	900-1800 LPM	3.50	FD-200	FD-S-200
FC-150	FC-S-150	1800-2700 LPM	3.50	FD-250	FD-S-250

[www.newage-india.in](http://www.newage-india.in)

**NEWAGE**<sup>®</sup>  
FIRE FIGHTING CO. LTD.

Address : "NKB House", P. O. Box No.: 14, Mehta Market, Surendranagar - 363 001, Gujarat, India  
Phone No. : +91 2752 288 000, +91 99250 63730 | Fax : +91 11 66173355 | Email : info@newage-india.in